



### KEY FEATURES


- Entry door framing system designed to accept heavy duty 50mm thick commercial swing doors.
- These heavy duty 50mm thick commercial doors are ideal for oversize door panels.
- Series 52 swing doors will accept 24mm thick insulating glass.
- Four midrail sizes to choose from (50, 115, 125 and 200mm deep).
- Two door thresholds designed to keep water out cover both internal and external swing hinged doors.
- Sub-sills available for high performance installations.
- Snap-fit nailing fin adaptor for brick veneer and cavity brick installations.
- Sidelights will accept awning and/or casement sashes.
- Recessed clean fixed sidelights and highlights pocket glazed similar to commercial framing.
- Can be fitted with hinged flydoors within the main frame.




Unique double-sided door stops allow for easy fitting of hinged screen doors.



Externally opening door sill.



Internally opening door sill.



Custom true French meeting stiles designed to improve water resistance.

#### GENERAL

**Max Panel Height\***  
3000mm

**Max Panel Width\***  
1200mm

**Max Glass Thickness**  
24mm

**Frame Depth**  
150mm

#### ENERGY

**UW Range**  
3.0-5.9

**SHGC Range**  
0.14-0.60

#### WEATHER

**Maximum Water**  
300 Pa. (open out)  
150 Pa. (open in)

#### ACOUSTICS

This product has not been acoustics tested.



\*Dimensions subject to individual site conditions. Liveable housing compliance requires the use of ramped sill option. BAL-40 compliance may limit glass options. Maximum glass size for BAL-40 products is 5m<sup>2</sup>.  
[elevatealuminium.com.au/650](http://elevatealuminium.com.au/650)