


KEY FEATURES


- Top Hung Sliding Door system which offers a wheelchair compliant sill in accordance with Australian Standard AS1428.1 for wheelchair accessibility.
- The custom Centor E3 quad rollers are fully adjustable up and down when doors are in the frame and are capable of supporting panels up to 320kg.
- Tested for compliance with the relevant Standards.
- The extra strong multi hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas, refer panel strength tables earlier in this Section.
- There are a large variety of door combinations (XF, FX, FXXF, XXF, FXX, FXXXXF and cavity sliding doors).
- Compatible with Centor S4 screens.
- Square clean lines with soft radius edges on internal meeting stile corners.
- With the correct glass, glass size, seals, and hardware, Series 704T can achieve BAL40 certification.




For the ultimate architectural look the 704T head can be recessed during installation for a minimal appearance.



The sill incorporates "Top Hat" feature which fills the recess in the sill to ensure disability access and minimise the risk of trips and falls - door panels glide over this rail.



Can be installed with a FlowTHRU™ drain for the ultimate flush threshold solution.



Doors run on heavy duty overhead rollers, delivering smooth, reliable operation

Max panel weight: 320kg

GENERAL

Max Frame Height*
3300mm

Max Panel Width*
2500mm

Max Glass Thickness
24mm

Frame Depth
Various

ENERGY

UW Range
2.3-6.2

SHGC Range
0.15-0.66

WEATHER

Maximum Water
300 Pa. (35mm Sill)

450 Pa. (55mm Sill)

ACOUSTICS**

6.38mm Lam
Rw30 (0;-1)

10.38mm Lam
Rw31 (-1;-1)

10.5mm VLam Hush™
Rw33 (0;-2)

24.38mm IGU with 6.38mm lam
Rw33 (-1;-3)

24.38mm IGU with 10.38mm lam
Rw35 (0;-2)



*Dimensions subject to individual site conditions. ** Based on tests carried out on the standard Series 704 door BAL-40 compliance may limit glass options. Maximum glass size for BAL-40 products is 5m².

elevatealuminium.com.au/704T