


KEY FEATURES


- This high-performance sliding door has been tested for compliance with the relevant Australian Standards.
- The extra strong multi-hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas.
- There are a large variety of door combinations possible. XF, FX, FXF, FXXF, XXF, FXX, XXXF, FXXX, FXXXXXXF and FXXXXXF. 90° corner units FX^XF and FXX^XXF are also available.
- Doors can be fitted with surface mounted deadlock, mortice lock or multi-point mortice lock.
- Doors run on heavy duty double or quad bogey wheel carriages up to 300kg on heavy duty quad rollers.
- Variety of bottom rail and midrail sizes available. The tall square bottom rail is standard.
- Thresholds and snap-in flat filler ensure that the clean looks are maintained.
- Doors can be fitted with external sliding or internal Centor™ S4 retractable roller fly doors.
- This standard Series 704 is not tested to BAL40. Refer to Series 704B.




A unique, self-draining sub-sill is a feature of the 704.



The image above shows ICON™ recessed pull handle option used with commercial mortice lock. On heavy doors we recommend D-Pull handles.



We offer a variety of meeting stile combinations to cover most areas in Australia.



Standard tall, small, beveled and square rails are all an option. Standard tall square bottom rail illustrated above.

GENERAL

Max Frame Height*
3300mm

Max Panel Width*
2500mm

Max Glass Thickness
24mm

Frame Depth
Various

ENERGY

UW Range
2.3-6.2

SHGC Range
0.15-0.66

WEATHER

Maximum Water
300 Pa (35mm sill)

450 Pa (55mm sill)

600 Pa (70mm sill)

ACOUSTICS

6.38mm Lam
Rw30 (0;-1)

10.38mm Lam
Rw31 (-1;-1)

10.5mm VLam Hush™
Rw33 (0;-2)

24.38mm IGU with 6.38mm lam
Rw33 (-1;-3)

24.38mm IGU with 10.38mm lam
Rw35 (0;-2)



*Dimensions subject to individual site conditions.

elevatealuminium.com.au/704