



KEY FEATURES


- This high-performance awning and casement window has been designed to accept Truth™ hardware. This allows us to offer very large casements and awnings fitted with scissor type winders with jamb to stile latches that secure the sashes in the closed position.
- The extra strong sashes allow large sash windows to be fabricated for high wind load areas.
- The Truth™ hardware can resist very high negative wind loads with the use of winders and side latches.
- Hardware comes in standard E-GARD™ or for extreme locations we also offer 304 stainless steel stays.
- Casement sashes open to 90° and have an opening gap of approximately 80mm on the hinge side, this allows cleaning of external glass face from inside the building.
- Fixed lowlights/sidelights are designed around Series 406 single glazed and 426 double glazed FrontGLAZE™.
- Series 468 awning windows accept standard flyscreens. Casement windows accept flyscreens when used with Truth™ hardware.




Snap-in jamb adaptors make it possible to have SG or DG fixed highlights and/or lowlights within the same frame.



Will accept glass up to 24mm IGU.



Also available in 150mm frame – see Series 668.



Designed to suit AWS FrontGLAZE™ framing systems

GENERAL

Max Panel Height*

Various

Max Panel Width*

Various

Max Glass Thickness

24mm

Frame Depth

102mm

ENERGY

UW Range

4.0-6.9

SHGC Range

0.14-0.52

WEATHER

Maximum Water

450 Pa.

ACOUSTICS

6.5mm VLam Hush™ /10mm

Air/8.5mm VLam Hush™

Rw41 (-1;-5)

6mm Tgh/12mm Air/ 6.5mm

VLam Hush™

Rw40 (-1;-5)

6.5mm VLam Hush™

Rw35 (-1;-4)

Based on test carried out on Series 466 awning windows.



*Dimensions subject to individual site conditions. A = Awning Configuration. C = Casement Configuration.

elevatealuminium.com.au/468