



KEY FEATURES


- The 704iD is a bottom-rolling sliding door designed for internal applications. **Not for use on the external wall.**
- Available in 102mm, 150mm, 200mm and 50mm single track.
- The low sill line is disability access compliant under AS1428.
- Available in a variety of configurations including cavity door.
- Clean square lines with soft radius edges on meeting stile corners. Pocket fillers on head, sill and jambs keep the visual appearance consistent throughout the door.
- Can be fitted with an array of custom mortice locks, recessed finger pulls and pull handles.



Strengthen rail for large panels, tracks can be ganged together for multi-stacking door applications.



Sill tracks can be configured so that tracks are only present where sliding or fixed panels exist. Designed to be recessed completely into the floor.



Flush sill with disability access compliance, running track is protected from damage.

GENERAL

Max Frame Height*
3000mm

Max Panel Width*
2000mm

Max Glass Thickness
24mm

Frame Depth
Various

ENERGY

UW Range
N/A

SHGC Range
N/A

WEATHER

Maximum Water
N/A

ACOUSTICS

6.38mm Lam Rw30 (0;-1)

10.38mm Lam Rw31 (-1;-1)

10.5mm VLam Hush™
Rw 33 (0;-2)

24.38mm IGU with 6.38mm lam Rw33 (0;-2)

24.38mm IGU with 10.38mm lam Rw 35 (0;-2)



*Dimensions subject to individual site conditions.

elevatealuminium.com.au/704iD